

rayMAX 25

INFRA-RED PRODUCT RANGE

The RAYMAX series of High Performance Infra-Red LED illuminators provide class leading performance, long life and ultra low maintenance. They incorporate the very latest surface mount LED's to deliver excellent night-time pictures with improved optical output and outstanding reliability.


Purpose designed to provide even output illumination, RAYMAX 25 is available in a number of different fixed angle variations to handle most standard installations.

Each unit is fitted with a Cool Running™ thermal management system to carefully control LED output and delivers a projected working life of 10 years.

RAYMAX illuminators are supplied with bracket and power supply. Control features on the power supply include adjustable power output, photocell and telemetry control. RAYMAX 25 is suitable for all low light installations up to 35 metres (115ft).

RAYMAX 25 is also available with low voltage PSU.

APPLICATIONS



POWERFUL

- Distances up to 35m (115ft)
- Latest LED technology
- High power - low running costs

FLEXIBLE

- Various angles (10°, 30°, 50° or 120°)
- Fully Controllable Power Supply
- Optional Low Voltage PSU

RELIABLE

- 10 year life
- Cool Running™ thermal management system
- Vandal resistant

CONTROLLED

- Zero Light Pollution
- Even Output Illumination
- Semi-Covert (850nm) or Covert (950nm) Options

rayTEC[®]

www.rayteccctv.com



ADAPTIVE ILLUMINATION™

Adaptive Illumination™ allows the installer to adjust the angle of the light projection from a single unit to fit the specific demands of any installation. Adjustment is quick and convenient and any angle upto 180 degrees (depending on model) is easily selectable. Adaptive Illumination is patent pending technology available exclusively from Raytec.



COOL RUNNING™ Thermal Management System

Cutting edge materials science techniques have been employed to improve thermal efficiency throughout the unit. Cool Running™ is specifically designed to allow all Raytec LED products to provide exceptionally long life - up to 10 years.



SMT (Surface Mount Technology)

The future of lighting is surface mount LED technology. Compared to standard through hole LED's, surface mount LED's are a more robust solution increasing reliability and improving product life. They are also far more efficient at the dissipation of heat allowing the LED's to run at higher power and achieve significantly improved performance.



VANDAL RESISTANT

The polycarbonate lens design protects against severe blows from crowbars, baseball bats and can even withstand successive shots from air pistols and rifles (range dependant).



ENERGY SAVING

All Raytec illuminators use high efficiency LED's and advanced control methods to deliver extremely low electrical consumption. Raytec illuminators are energy saving and deliver huge savings in running costs compared to traditional bulb illuminators.



HIGH DEFINITION LIGHTING


High Definition Lighting allows cameras to provide crystal clear, high signal images during the hours of darkness. The breakthrough in HD lighting is made possible with Raytec's high power LED technology delivering increased power on scene.

5 YEAR WARRANTY

All Raytec CCTV illuminators are provided with a 5 year warranty, unmatched anywhere in the CCTV lighting industry. Raytec illuminators provide guaranteed long life!



TECHNICAL SPECIFICATIONS



ILLUMINATOR

- Max Distance:* up to 35m (115ft)
- Angle:* 30, 50 or 120 degrees
- Optics:* SMT LED's
- Consumption:* 10W max
- Voltage:* 13.5V current controlled
- Weight:* 1.0kg
- Environmental:* IP66
- Temp Range:* -50 to +50°C (-58 to 122°F)
- Cable Length:* 2.5m
- Colour:* Black
- Wavelength:* 850 or 950nm
- Dimensions:* 75 x 100 x 54mm
3" x 4" x 2" approx

BRACKETRY

U Bracket included

POWER SUPPLY

- Input:* Universal 100-240V AC auto-sensing
- Output:* 10W max
- Temperature:* -50 to +50°C (-58 to 122°F)
- Weight:* 0.9Kg
- Dimensions:* 160mm x 120mm x 80mm
6" x 5" x 3" approx

Standard PSU (included)

Adjustable photocell
Adjustable power output for IR
Telemetry Control

Premium PSU (add ~PR to part code)

All standard PSU features PLUS:
Photocell following contact for switching of dual mode cameras
12V dc output to power cameras

Pulsed PSU (add ~PU to part code)

To pulse Raytec lights in sync with cameras.
Power Adjustment
Video In and Video Out connections to sync light and camera,
12V dc output to power cameras

PART CODES

RM25-10	RAYMAX 25, 10°	AI, 850nm + PSU
RM25-30	RAYMAX 25, 30°	AI, 850nm + PSU
RM25-50	RAYMAX 25, 50°	AI, 850nm + PSU
RM25-120	RAYMAX 25, 120°	AI, 850nm + PSU
RM25-10-C	RAYMAX 25, 10°	AI, 950nm + PSU
RM25-30-C	RAYMAX 25, 30°	AI, 950nm + PSU
RM25-50-C	RAYMAX 25, 50°	AI, 950nm + PSU
RM25-120-C	RAYMAX 25, 120°	AI, 950nm + PSU

DISTANCES

35m (115ft)
20m (66ft)
14m (46ft)
8m (26ft)
Contact Raytec
Contact Raytec
Contact Raytec
Contact Raytec



Europe / Middle East: Tel: +44 (0) 1670 528446
Americas: Tel: +1 281 438 3599

Email: sales@rayteccctv.com
Email: ussales@rayteccctv.com
Web: www.rayteccctv.com